

**IVECO SPECIFICATIONS**
**Eurocargo**

Model	ML140E22	ML150E24W	ML160E24	ML180E24K	ML180E28	AD190T38WH
<b>Dimensions (mm)</b>						
OL Overall Length	9 232	7 477	10 042	6 205	9 901	7 862
OW Overall Width	2 295	2 490	2 295	2 390	2 390	2 550
OH Overall Height	2 737	3 072	2 757	2 826	2 837	3 237
FOH Front Overhang	1 362	1 387	1 362	1 362	1 362	1 440
ROH Rear Overhang	2 685	1 935	3 000	1 133	2 235	1 780
WB Wheelbase	5 175	4 150	5 670	3 690	6 210	4 500
BBC Bumper to Back of Cab	1 610	1 610	1 610	1 610	1 610	1 885
CA Cab to Rear Axle / Unit	4 910	3 920	5 405	3 425	5 945	4 055
TD Turning Diameter (wall to wall)	17 740	16 520	19 260	14 390	22 110	18 900
<b>Mass Data (kg)</b>						
GVM Manufacturer's Gross Vehicle Mass	14 000	15 000	16 000	18 000	18 000	18 000/20 000
GCM Manufacturer's Gross Combination Mass	17 500	18 500	26 500	22 500	32 500	55 000
GA Manufacturer's Front Axle Mass	5 100	5 700	6 100	7 500	7 500	9 000
GA/GAU Manufacturer's Rear Axle Mass	9 500	10 000	11 000	11 500	11 500	9 000/13 000
V Permissible Maximum Vehicle Mass	14 100	14 700	15 100	16 500	16 500	16 700
AF Permissible Maximum Front Axle Mass	5 100	5 700	6 100	7 500	7 500	7 700
AR Permissible Maximum Rear Axle Mass	9 000	9 000	9 000	9 000	9 000	9 000
UF Unladen Front Axle Mass	3 060	3 860	3 125	3 400	3 670	5 060
UR Unladen Rear Axle Mass	1 530	1 530	1 530	1 530	1 530	2 600
UT Total Unladen Mass	4 590	5 390	4 655	4 930	5 200	7 660
D/T Permissible Max Drawing Vehicle Mass	17 500	18 500	26 500	22 500	32 500	55 000
<b>Engine</b>						
Make	Iveco	Iveco	Iveco	Iveco	Iveco	Iveco
Model Configuration	Inline straight six	Inline straight six	Inline straight six	Inline straight six	Inline straight six	straight engine
Capacity	5 880 cc	5 880 cc	5 880 cc	5 880 cc	5 880 cc	6 inline cylinders, 12,880 cc
Max Power (kW @ revs/min)	162@2700	176@2700	176@2700	176@2700	202@2700	279@1500-1900
Max Torque (Nm @ revs/min)	680@1200-2 100	810@1250	810@1250	810@1250	930@1200-2100	1800@900-1400
<b>Gearbox</b>						
Make / Model	Mechanical ZF 6S 700 TO	Mechanical ZF 6S 800 TO	Mechanical ZF 9S 750TO	Mechanical ZF 6S 800 TO	Manual ZF 9S 750TO	Eurotronic 16AS2630 TO/ Mechanical 16S2220 TO
No of Gears	6	6	9	6	9	16
High and Low ratios	0,79 and 6,02	0,78 and 6,58	1 and 13,16	0,78 and 6,58	1 and 13,16	0,83/0,84 and 14,12/13,8
Synchromesh or Constantmesh	Synchromesh	Synchromesh	Synchromesh	Synchromesh	Synchromesh	Synchromesh
Rear Axle Ratio	4,63	6,95	5,63	6,14	4,89	5,01/4,67
Drive	4x2	4x4	4x2	4x2	4x2	4x4
Rear axle Distance apart	N/A	N/A	N/A	N/A	N/A	n/a
Retarder	No	No	No	No	No	n/a
<b>Standard Tyre Equipment</b>						
Size and ply rating	10R22,5	14R20	11R22,5	315/80R22,5	315/80R22,5	14R20
Radial or crossply	Radial	Radial	Radial	Radial	Radial	Radial





# IVECO

SCAN HERE TO  
FIND OUT MORE  
ABOUT IVECO

Trakker			Stralis			X-Way
AD380T42H	AD380T42WH	AD410T42H	AT440T44TH	AS750S48TZP	AT700S43TZP	AD260S35HZ
9 527	8 267	9 482	6 844	6 815	6 815	6 931
2 550	2 550	2 550	2 550	2 550	2 550	2 550
3 106	3 234	3 147	3 096*	3 822	3 625	3 068
1 440	1 440	1 440	1 440	1 410	1 410	1 410
2 080	1 850	1 495	785	778	778	775
4 500	3 820	5 020	3 200	3 200	3 200	3 200-5 100
1 885	1 885	2 025	2 380	2 380	2 380	1 885
4 745	4 065	5 125	4 830	2 950	2 950	3 445-5 345
19 150	19 900	20 450	16 600	15 980	15 980	16 200
38 000	38 000	41 000	26 000	26 000	26 000	26 000
60 000	100 000	70 000	60 000	75 000	70 000	44 000
9 000*	9 000 *	18 000 *	8 000	8 000	7 500	8 000
29 200**	30 000 **	29 200 **	21 000	21 000	21 000	21 000
25 700	25 700	33 400	25 700	25 700	25 700	25 700
18 000	18 000	18 000	18 000	7 700	7 700	7 700
7 700	7 700	15 400	7 700	18 000	18 000	18 000
4 765	5 080	6 895	4 885	4 890	4 635	4 155
4 885	5 120	3 815	4 295	3 650	3 625	3 545
9 650	10 200	10 710	9 180**	8 540	8 260	7 700
56 000	56 000	56 000	56 000	56 000	56 000	44 000
Iveco straight engine 6 inline cylinders,12,880 cc 309@1500-1900 1900@900-1500	Iveco straight engine 6 inline cylinders,12,880 cc 309@1500-1900 1900@900-1500	Iveco straight engine 6 inline cylinders,12,880 cc 309@1500-1900 1900@900-1500	Iveco straight engine 6 inline cylinders,12,880 cc 324@1450-1900 2100@ 900-1470	Iveco straight engine 6 inline cylinders, 12,880 cc 354@1540-1900 2200@1000-1540	Iveco straight engine 6 inline cylinders 10,300 cc 316@1590-2100 1900@1050-1590	Iveco straight engine 6 inline cylinders, 7,790 cc 259@2400 1280@1080-1930
Eurotronic 16AS2630 TO	Eurotronic 16AS2630 TO	Eurotronic 16AS2630 TO	Eurotronic 12AS2330 TD	Eurotronic 12AS2330 TD	Eurotronic 12AS1930TD	Eurotronic 12AS1930TD
16	16	16	12	12	12	12
0,83 and 14,12	0,83 and 14,12	0,83 and 14,12	1 and 15,86	1 and 15,86	1 and 15,86	1 and 15,86
Synchromesh 4,67 6x4 1380 ZF Intarder	Synchromesh 5,01 6x4 1380 n/a	Synchromesh 4,23 8x4/4 1380 ZF Intarder	Synchromesh 4,125 6x4 1380 ZF Intarder	Synchromesh 6x4 1395 ZF Intarder	Synchromesh 6x4 1395 ZF Intarder	Synchromesh 6x4 1380 No
315/80R22,5	14R20 single	385/65R22,5	315/80R22,5	315/80R22,5	385/65R22,5/ 315/80R22,5	315/80R22,5
Radial	Radial	Radial	Radial	Radial	Radial	Radial



**IVECO SPECIFICATIONS**
**Daily Van**
**Daily CH**

Model	35S17A8V	50C17A8V	65C15V	70C15V	35S13A8	35S17A8
<b>Dimensions (mm)</b>						
OL Overall Length	5 709	7 274	7 659	7 659	6 523	6 563
OW Overall Width	2 010	2 010	2 010	2 052	2 010	2 010
OH Overall Height	2 660/2 280	2 740	2 850	3 050	2 235	2 233
FOH Front Overhang	1 048	1 048	1 048	1 048	1 048	1 048
ROH Rear Overhang	1 141	2 126	2 511	2 511	1 765	1 765
WB Wheelbase	3 520	4 100	4 100	4 100	3 750	3 750
BBC Bumper to Back of Cab	2 298	2 298	2 298	2 298	2 418	2 418
CA Cab to Rear Axle / Unit	n/a	n/a	n/a	n/a	2 340	2 340
TD Turning Diameter (wall to wall)	12 084	14 564	14 108	14 108	12 764	12 764
<b>Mass Data (kg)</b>						
GVM Manufacturer's Gross Vehicle Mass	3 490/3 600	5 400	6 500	7 000	3 490/3 600	3 490/3 600
GCM Manufacturer's Gross Combination Mass	7 000	8 700	10 000	10 500	7 000	7 000
GA Manufacturer's Front Axle Mass	1 900	2 100	2 300	2 500	1 900	1 900
GA/GAU Manufacturer's Rear Axle Mass	2 240	3 700	5 000	5 350	2 240	2 240
V Permissible Maximum Vehicle Mass	3 490/3 600	5 400	6 500	7 000	3 490/3 600	3 490/3 600
AF Permissible Maximum Front Axle Mass	1 900	2 100	2 300	2 500	1 900	1 900
AR Permissible Maximum Rear Axle Mass	2 240	3 700	5 000	5 350	2 240	2 240
UF Unladen Front Axle Mass	1 280/1 332	1 383	1 487	1 515	1 335	1 366
UR Unladen Rear Axle Mass	915/899	1 158	1 466	1 554	457	456
UT Total Unladen Mass	2 195/2 231	2 541	2 953	3 069	1 708	1 822
D/T Permissible Max Drawing Vehicle Mass	6 990/7 100	8 700	10 000	10 500	7 000	7 000
<b>Engine</b>						
Make	FPT Industrial	FPT Industrial	FPT Industrial	FPT Industrial	FPT Industrial	FPT Industrial
Model Configuration	straight engine	straight engine	straight engine	straight engine	straight engine	straight engine
Capacity	4 inline cylinders; 2,998 cc	4 inline cylinders; 2,998 cc	4 inline cylinders; 2,998 cc	4 inline cylinders; 2,998 cc	4 inline cylinders; 2,287 cc	4 inline cylinders; 2,998 cc
Max Power - kW @ r/min	93@3600	93@3600	107@3000-3500	107@3000-3500	96@3000-3600	125@3000-3500
Max Torque - Nm @ r/min	320@1800 - 2750	320@1800 - 2750	350@1400 - 2600	350@1400 - 2600	320 @1800 - 3500	425@1250 - 2600
<b>Gearbox</b>						
Make / Model	Automatic ZF 8HP	Automatic ZF 8HP	Manual 2840.6 OD	Manual 2840.6 OD	Automatic ZF 8HP	Automatic ZF 8HP
No of Gears	6	6	6	6	6	6
High and Low ratios	0,791 and 5,375	0,791 and 5,375	0,791 and 5,375	0,791 and 5,375	0,791 and 5,375	0,791 and 5,375
Synchromesh or Constantmesh	Synchromesh	Synchromesh	Synchromesh	Synchromesh	Synchromesh	Synchromesh
<b>Rear Axle Ratio</b>						
Drive	4x2	4x2	4x2	4x2	4x2	4x2
Retarder	No	No	No	No	No	No
<b>Standard Tyre Equipment</b>						
Size and ply rating	235/65 R 16	195/75 R 16	225/75 R 16	225/75 R 16	225/65/R15	225/65/R16
Radial or crossply	Radial	Radial	Radial	Radial	Radial	Radial







# IVECO

SCAN HERE TO  
FIND OUT MORE  
ABOUT IVECO

massis cab

Daily 4x4

MINIBUS

50C17A8	70C15/D	55S15E3A8 WX	55S15E3A8 D WX	70S15E3A8 WX	55C15E3A8 V WX	50C15V-22+1 seater	65C15V- 25+1 Seater
7 413	7413	5 348	5 853	6 818	7 179	7 274	7 659
2 010	2052	2 056	2 057	2 056	2 049	2 010	2 052
2 263	2347	2 522	2 515	2 501	2 806	2 740	2 850
1 048	1048	928	928	928	928	1 048	1 048
2 015	2015	940	1 145	1 715	2 076	2 126	2 511
4 350	4350	3 480	3 780	4 175	4 175	4 100	4 100
2 418	2418	2 368	3 164	2 368	2 314	n/a	n/a
2 940	2190	1 990	1 544	2 685	n/a	n/a	n/a
15 348	14866	14 100	14 900	16 100	16 300	14 564	14 108
5 400	7200	5 500	5 500	7 000	5 500	5 400	6 500
8 700	10500	9 000	9 000	10 500	9 000	8 700	10 000
2 100	2500	2 450	2 450	2 700	2 450	2 100	2 300
3 700	5350	3 700	3 700	5 000	3 700	3 700	5 000
5 400	7200	5 500	5 500	7 000	5 500	5 400	6 500
2 100	2500	2 450	2 450	2 700	2450	2 100	2 300
3 700	5350	3 700	3 700	5 000	3 700	3 700	5 000
1 439	1644	1 885	2 075	1 900	1 775	1 590	1 749
657	950	983	1 168	1 000	1 762	2 045	2 367
2 096	2594	2 868	3 243	2 900	3 537	3 635	4 116
8 700	10 500	9 000	9 000	10 500	9 000	8 700	10 000
FPT Industrial straight engine	FPT Industrial straight engine	FPT Industrial straight engine	FPT Industrial straight engine	FPT Industrial straight engine	FPT Industrial straight engine	FPT Industrial straight engine	FPT Industrial straight engine
4 inline cylinders; 2,998 cc	4 inline cylinders; 2,998 cc	4 inline cylinders; 2,998 cc	4 inline cylinders; 2,998 cc	4 inline cylinders; 2,998 cc	4 inline cylinders; 2,998 cc	4 inline cylinders; 2,998 cc	4 inline cylinders; 2,998 cc
125@3000-3500	107@3000-3500	107@3000-3500	107@3000-3500	107@3000-3500	107@3000-3500	107@3000-3500	107@3000-3500
425@1250 - 2600	350@1400 - 2600	350@1400 - 2600	350@1400 - 2600	350@1 400 - 2 600	350@1 400 - 2 600	350@1400 - 2600	350@1400 - 2600
Automatic ZF 8HP	Manual 2840.6 OD	Hi-MATIC 8HP70L	Hi-MATIC 8HP70L	Hi-MATIC 8HP70L	Hi-MATIC 8HP70L	Manual 2840.6 OD	Manual 2840.6 OD
6	6	8	8	8	8	6	6
0,791 and 5,375	0,791 and 5,375	0,667-D.O.D and 4,696	0,667-D.O.D and 4,696	0,667-D.O.D and 4,696	0,667-D.O.D and 4,696	0,791 and 5,375	0,791 and 5,375
Synchromesh	Synchromesh	Synchromesh	Synchromesh	Synchromesh	Synchromesh	Synchromesh	Synchromesh
4:44	4:3	5:13	5:13	5:13	3:91	4:44	4:3
4x2	4x2	4x4	4x4	4x4	4x4	4x2	4x2
No	No	No	No	No	No	No	No
195/75R16	225/75R16	265/70R19,5	265/70R19,5	265/70R19,5	225/75R16	195/75R16	225/75R16
Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial





## IVECO SPECIFICATIONS

	Afriway Bus	
Model	18.28A	26.28A
<b>Dimensions (mm)</b>		
Overall Length	12 210	13 990
Overall Width	2 600	2 600
Overall Height	3 663	3 663
Front Overhang	2 605	2 605
Rear Overhang	3 395	3 770
Wheel base	6 210	6 210
Bumper to Back of Cab	N/A	N/A
Cab to Rear Axle / Unit	N/A	N/A
Turning Diameter(wall to wall)	18,9	23,58
<b>Mass Data (kg)</b>		
Manufacturer's Gross Vehicle Mass	18 000	26 000
Manufacturer's Gross Combination Mass	22 500	29 000
Manufacturer's Front Axle Mass	7 500	7 500
Manufacturer's Rear Axle Mass	11 500	11 500+8 000
Permissible Maximum Vehicle Mass	25 400	25 400
Permissible Maximum Front Axle Mass	7 500	7 500
Permissible Maximum Rear Axle Mass	10 200	10 200+8 000
Unladen Front Axle Mass	5 015	5 220
Unladen Rear Axle Mass	5 265	5 420+2 480
Total Unladen Mass	13 160	13 160
Permissible Max Drawing Vehicle Mass	22 500	28 900
<b>Engine</b>		
Make	Iveco	Iveco
Model Configuration	Inline straight six	Inline straight six
Capacity	5 880 cc	5 880 cc
Max Power (kW @ revs/min)	202@2 500	202@2 500
Max Torque (Nm @ revs/min)	930@1 250-2 100	930@1 250-2 100
<b>Gearbox</b>		
Make / Model	Auto Voith Diwa 854.5	Auto Voith Diwa 854.5
No of Gears	4	4
<b>High and Low ratios</b>		
Synchromesh or Constantmesh	N/A	N/A
Rear Axle Ratio	5,63	6,14
Drive	4x2	6x2
Rear axle Distance apart	N/A	1 395
Retarder	Yes	Yes
<b>Standard Tyre Equipment</b>		
Size and ply rating	315/80R22,5	315/80R22,5
Radial or crossply	Radial	Radial

